





Series standard

Air / water / hydraulic

Series 805	Dimension	Length (m)	Hose	Media	Max. Pressure	Inlet	Outlet	Weight	Item	Pack. Dim.(mm)	
	3/8"	10	rubber	air/water	20 bar	F 3/8" G	M 3/8" G	16 kg	E805103-N	430x225x465	
	Swivel bracket 140°								3 kg	E800100-N	250x200x140
	Specifications * Heavy-duty steel construction with corrosion resistant powder coating * Solid 1" steel centre support shaft * Full flow solid brass swivel joint * Multi-position release ratchet spring fully enclosed * Four direction non-snap rollers reduce hose wear abrasion * Wall, ceiling or floor mount										





Series 809	Dimension	Length (m)	Hose	Media	Max. Pressure	Inlet	Outlet	Weight	Item	Pack. Dim.(mm)	
	1/4"	10	rubber	air/water	20 bar	F 1/4" G	M 1/4" G	13 kg	E809102	400x180x430	
	3/8"	10	rubber	air/water	20 bar	F 3/8" G	M 3/8" G	14 kg	E809103	400x180x430	
	10/14,5mm	12	PU	air	20 bar	F 3/8" G	M 3/8" G	15 kg	E809123	400x180x430	
	Swivel bracket 140°								2,5 kg	E800809	250x200x140
	High Pressure										
	1/4"	8	rubber	grease/Hydraulic	345 bar	F 1/4" G	M 1/4" G	15 kg	EH809082	400x180x430	
	3/8"	8	rubber	grease/Hydraulic	276 bar	F 3/8" G	M 3/8" G	17 kg	EH809083	400x180x430	
Specifications * Heavy-duty steel construction with corrosion resistant powder coating * Four direction non-snap rollers reduce hose wear abrasion * Multi-position ratchet lock and easy tension adjustment * Guide arm adjustable for handling up to 9 positions permits wall, ceiling or floor mount											

Series 816	Dimension	Length (m)	Hose	Media	Max. Pressure	Inlet	Outlet	Weight	Item	Pack. Dim.(mm)
	10/14,5mm	15	PU	air	20 bar	F 3/8" G	M 3/8" G	13 kg	E816153	460x190x490
	Specifications * Heavy-duty steel construction with corrosion resistant powder coating * Guide arm adjustable for handling up to 9 positions permits wall, ceiling or floor mount * PU braided hose									

Series 820	Dimension	Length (m)	Hose	Media	Max. Pressure	Inlet	Outlet	Weight	Item	Pack. Dim.(mm)	
	3/8"	15	rubber	air/water	20 bar	F 3/8" G	M 3/8" G	22 kg	E820153	500x230x520	
	1/2"	15	rubber	air/water	20 bar	F 1/2" G	M 1/2" G	23 kg	E820154	500x230x520	
	Swivel bracket 140°								2,5 kg	E800820	245x195x135
	Specifications * Heavy-duty steel construction for long life in industrial an automotive applications * Reel covered by corrosion resistant powder coating, two supporting arm and base galvanized * Dual pedestal base, double supporting 1-3/8" axle, full flow shaft & swivel joint, structurally reinforced * Multi position release ratchet, spring fully enclosed and lubricated * Four direction non-snap rollers reduce hose wear abrasion * Wall, ceiling or floor mount										

Series standard


Air / water / hydraulic


Series 801	Dimension	Length (m)	Hose	Media	Max. Pressure	Inlet	Outlet	Weight	Item	Pack. Dim.(mm)	
	3/8"	20	rubber	air/water	20 bar	F 3/8" G	M 3/8" G	22 kg	E801203-N	520x235x560	
	1/2"	20	rubber	air/water	20 bar	F 1/2" G	M 1/2" G	26 kg	E801204-N	520x235x560	
	Swivel bracket 140°								3 kg	E800100-N	245x195x135
	Specifications * Steel construction with corrosion resistant powder coating * Solid 1" steel centre support shaft * Full flow solid brass swivel joint * Multi-position release ratchet spring fully enclosed * Four direction non-snap rollers reduce hose wear abrasion * Wall, ceiling or floor mount										
Series 808	Dimension	Length (m)	Hose	Media	Max. Pressure	Inlet	Outlet	Weight	Item	Pack. Dim.(mm)	
	3/8"	20	rubber	air/water	20 bar	F 3/8" G	M 3/8" G	26 kg	E808203	520x235x565	
	1/2"	20	rubber	air/water	20 bar	F 1/2" G	M 1/2" G	31 kg	E808204	520x235x565	
	Swivel bracket 140°								2,5 kg	E800808	245x195x135
	High Pressure										
	3/8"	20	rubber	grease/Hydraulic	276 bar	F 3/8" G	M 3/8" G	35 kg	EH808203-VI	520x235x565	
3/8"	20	without hose	grease/Hydraulic	276 bar	F 3/8" G	-	22 kg	EH808203W/O-VI	520x235x565		
Specifications * Heavy-duty steel construction with corrosion resistant power coating * 7" wide L-Shaped base with groove reinforcement ensures stable support * Multi-position ratchet lock and easy tension adjustment * Guide arm adjustable for handling up to 9 positions permits wall, ceiling or floor mount											
Series 880	Dimension	Length (m)	Hose	Media	Max. Pressure	Inlet	Outlet	Weight	Item	Pack. Dim.(mm)	
	1/2"	30	rubber	air/water	20 bar	F 1/2" G	M 1/2" G	56 kg	E880304	662x340x765	
	3/4"	20	rubber	air/water	20 bar	F 3/4" G	M 3/4" G	58 kg	E880206	662x340x765	
	1"	15	rubber	air/water	20 bar	F 1" G	M 1" G	60 kg	E880158	662x340x765	
	1/2"	30	without hose	air/water	200 bar	F 1/2" G	-	43 kg	EM880304W/O	662x340x765	
	3/4"	20	without hose	air/water	200 bar	F 3/4" G	-	45 kg	EM880206W/O	662x340x765	
	1"	15	without hose	air/water	200 bar	F 1" G	-	47 kg	EM880158W/O	662x340x765	
	Specifications * Heavy-duty steel construction with corrosion resistant powder coating * Four direction non-snap rollers reduce hose wear abrasion * Spring fully enclosed and lubricated * Guide arm adjustable, floor mount										
Series EW808	Dimension	Length (m)	Hose	Media	Max. Pressure	Inlet	Outlet	Weight	Item	Pack. Dim.(mm)	
	1/4"	20	rubber	oxygen - acetylene	20 bar	F 1/4" G	M 1/4" G	28 kg	EW8082022	552x250x565	
	Specifications * Heavy-duty steel construction with corrosion resistant powder coating * Full flow swivel joint and swivel body are made from drop forging brass * Double "O" ring sealed design prevents leakage * Swivel body and inlet are both permanently identified with machined grooves on the acetylene side to assure proper installation * 36" inlet hose assembly standard										


Series standard


in painted steel
Air / water
20 bar

Swivel: Brass
Seals: Viton
Hose: Polyurethane

Series 270	Dimension	Length (m)	Hose	Flow	Inlet	Outlet	Item
	Without hose	-	-	800 l/min	M 3/8" G	F 3/8" G	I268/10
	10/14,5mm	13	PU	690 l/min	M 3/8" G	M 3/8" G	I268/12
	8/12mm	15	PU	320 l/min	M 3/8" G	M 1/4" G	I268/13
	6/10mm	10	PU	280 l/min	M 3/8" G	M 1/4" G	I268/14
	6/10mm	15	PU	250 l/min	M 3/8" G	M 1/4" G	I268/15

Series 300	Dimension	Length (m)	Hose	Flow	Inlet	Outlet	Item
	Without hose	-	-	800 l/min	M 3/8" G	F 3/8" G	I298/10
	10/14,5mm	15	PU	670 l/min	M 3/8" G	M 3/8" G	I298/12
	8/12mm	18	PU	300 l/min	M 3/8" G	M 1/4" G	I298/13
	13/19mm	8	PU	800 l/min	M 1/2" G	M 1/2" G	I298/14
	13/19mm	12	PU	780 l/min	M 1/2" G	M 1/2" G	I298/15

Series 350	Dimension	Length (m)	Hose	Flow	Inlet	Outlet	Item
	Without hose	-	-	800 l/min	M 3/8" G	F 3/8" G	I348/10
	10/14,5mm	20	PU	650 l/min	M 3/8" G	M 3/8" G	I348/12
	8/12mm	20	PU	280 l/min	M 3/8" G	M 1/4" G	I348/13
	13/19mm	10	PU	780 l/min	M 1/2" G	M 1/2" G	I348/14
	13/19mm	15	PU	760 l/min	M 1/2" G	M 1/2" G	I348/15

Series 430	Dimension	Length (m)	Hose	Flow	Inlet	Outlet	Item
	Without hose	-	-	800 l/min	F 1/2" G	F 1/2" G	I430/10
	13/19mm	10	PU	760 l/min	F 1/2" G	M 1/2" G	I428/11
	13/19mm	15	PU	740 l/min	F 1/2" G	M 1/2" G	I428/12



Fixed and swivelling bracket see page 40-41