

Industrial Series

in painted steel
Grease
600 bar

Swivel: Steel
Seals: Polyurethane
Hose: Black synthetic rubber



S. 540



S. 430



S. 300

	Dimension	Length (m)	Hose	Flow	Inlet	Outlet	Item
Series 300	Without hose	-	-	1200 g/min	F 3/8" G	F 3/8" G	I300/50
	1/4"	12	rubber	650 g/min	F 3/8" G	M 1/4" G	I300/51
Series 350	Without hose	-	-	1200 g/min	F 3/8" G	F 3/8" G	I350/50
	1/4"	12	rubber	650 g/min	F 3/8" G	M 1/4" G	I350/51
	1/4"	16	rubber	550 g/min	F 3/8" G	M 1/4" G	I350/52
Series 430	Without hose	-	-	1200 g/min	F 3/8" G	F 1/2" G	I430/50
	1/4"	12	rubber	650 g/min	F 3/8" G	M 1/4" G	I430/51
	1/4"	18	rubber	550 g/min	F 3/8" G	M 1/4" G	I430/52
	3/8"	10	rubber	800 g/min	F 3/8" G	M 1/4" G	I430/55
	3/8"	15	rubber	750 g/min	F 3/8" G	M 1/4" G	I430/56
Series 530	Without hose	-	-	1200 g/min	F 3/8" G	F 1/2" G	I530/50
	3/8"	20	rubber	600 g/min	F 3/8" G	M 1/4" G	I530/51
	3/8"	25	rubber	500 g/min	F 3/8" G	M 1/4" G	I530/52
Series 540	Without hose	-	-	1200 g/min	F 3/8" G	F 1/2" G	I540/50
	3/8"	30	rubber	450 g/min	F 3/8" G	M 1/4" G	I540/51



Fixed and swivelling bracket see page 40-41